Adhesive Films, Inc. Product Data

Description	Product	ID #	‡ Melt Temp. (degrees F)	Recommemded Heat Sealing Temp.	•• STD Gauges	Resists: Plasticizers	Resists: Home Wash	Resists: Industrial Wash	Resists: Dry Clean	Shows Adhesion To: Fabrics: Polyester	Fabrics: Polycotton	Fabrics: Cotton	Fabrics: Nylon	Fabrics: Rayon	Fabrics: Lycra	Fabrics: Fiberglass	Plastics: ABS	Plastics: Polycarbonate	Plastics: Polyethylene	Plastics: Polypropylene	Plastics: PVC	Plastics: Polyurethane	Organics: Wood	Organics: Leather	Organics: Paper	Metals: Aluminum	Metals: Copper	Metals: Steel
Urethane Adhesive Films	UAF	406	190–210 (90–100)	250–300 (125–150)	.0015" .003" .005"	◆	◆		◆	◆	◆	◆	◆	◆	◆	◆	◆	◆			◆	◆	◆	◆	◆		◆	
	UAF	410	270–290 (135–145)	375–425 (190–210)	.003" .006"	◆	◆	◆	◆	◆	◆	◆			◆	◆	◆				◆	◆	◆	◆	◆			
	UAF	438	170–190 (75–85)	250–300 (125–150)	.001"-.005"	◆	◆		◆	◆	◆	◆	◆	◆	◆	◆	◆	◆			◆	◆	◆	◆	◆	◆	◆	◆
	UAF	440	350–370 (170–180)	400–475 (205–225)	.0015" .005"	◆	◆	◆	◆		◆	◆				◆	◆				◆	◆	◆		◆		◆	
	UAF	442	270–290 (135–145)	375–425 (190–210)	.003" .004" .005"	◆	◆	◆	◆	◆	◆	◆			◆	◆	◆	◆			◆	◆	◆	◆	◆		◆	
	UAF	444	170–190 (75–85)	250–300 (125–150)	.003" .005"	◆	◆		◆	◆	◆	◆	◆	◆	◆	◆	◆	◆			◆	◆	◆	◆	◆	◆	◆	◆
	UAF	472	190–210 (90–100)	250–300 (125–150)	.001"-.003" .005"	◆	◆		◆		◆	◆	◆	◆	◆	◆	◆	◆			◆	◆	◆	◆	◆	◆	◆	◆

KEY:

•• STD gauges: Refers to total thickness of adhesive

◆ **:** Very good to excellent adhesion

If you require a non-standard thickness or color pigmented adhesive film, we will be happy to discuss your specific needs.

ADHESIVE FILMS, INC.

www.adhesivefilms.com